

FIG. 1




FIG. 2




FIG. 3




FIG. 4

#	Parameter	Min	Тур	Max	units
T1	Clock/Date Pulse Width		100		ns
T2	Clock Pulse to Clock Pulse		125		шs
T3	Clock Pulse to Data Pulse (Data=1)		62.5		шs
T4	Pulses in a Burst	17		33	#
T5	Burst Width		2		ms
T6	Burst to Burst	8	16	24	ms

FIG. 5

D0 D15 D14 D13 D12 D11 D10 D9 **BG D7** D6 **D5** D3 **D2** D1 **D4** RF **A7 A6 A5** A3 **A2 A1** Α0 Ack **S4 S3 S2 S1** S0 Technology Ability Field Selector Field

FIG. 6

D 1 0	D 9	D 8	D 7	D 6	Description
0	0	0	0	1	10BASE-T
0	0	0	1	٥	10BASE-T Full Duplex
0	0	1	0	0	100BASE-TX
0	1	0	0	0	100BASE-TX Full Duplex
1	0	0	0	0	100BASE-T4

FIG. 7

D 1 0	9	D 8	D 7	D 6	Description
0	0	0	1	1	Regular and Full Duplex 10BASE—T
1	0	1	0	1	10BASE—T, 100BASE—TX, and 100BASE—T4 all supported in normal configurations.
0	0	1	0	1	10BASE—T and 100BASE—TX configurations both supported.
1	1	1	0	0	100BASE-TX,100BASE-T4,100BASE-TX Full Duplex supported.





FIG. 9



- Note Ability_match is 3 consecutive data pattern match, ignoring acknowledgment bit.
 - Acknowledge_match is 3 consecutive data patterns having acknowledgment bit set.
 - ack_cnt_done is from FLP Transmit SM to indicate completion of sending a minimum of 4-16 acknowledge patterns.
 - optional remote sensing capability, refer to Management support section.





FIG. 11






FIG. 13




FIG. 14




FIG. 15

Parameter	Min	Тур	Max	units
FLP_test_min_timer	5		25	มร
FLP_test_max_timer	165	·	185	ПZ
Link_test_min_timer	5		7	ms
Link_test_max_timer	50		150	ms
Data_detect_min_timer	15		47	มร
Data_detect_max_timer	78		110	แร

FIG. 16




FIG. 17




FIG. 18




FIG. 19

10/15 NSC1-54400




FIG. 20




FIG. 21




FIG. 22

11/15 NSC1-54400





FIG. 23A



Largone O.G. F.1G.

S. S. L. T. S. Market

FIG. 23C

Data Word Encoding (Multi-Protocol Negotiation)

	_	
00	0	
10	0	O,
D2	0	Selector/PID
D4 D3	0	Sele
04	0	
05	Ack	
90	Series End	
07	X1	
08	x2	
60	X3	
910	X4	Field
. 011	8	Ability Field
D13 D12	æ	
D13	8	
D14	RF	
015	N.P.	
•		1

ty Field (D7 to D13)	Number of Protocols 1 Reserved
Ability	D10:D7 D13:D11

Other Bits in the field	Acknowledge Bit	Series End Bit	Remote Fault	Next Page (N.P.)
Other.	05	90	014	015

00000 Multi-Protocol Negotiation 00001 CSMA/CD Compatible (D0=1; D4-D1=0; Protocol Discriminator (D4:D0) (Selector or PID)

FIG. 24

/




FIG. 25